

TATA MOTORS KA BHAROSA RAHE AAPKE SAATH HAR KADAM



TATA MOTORS
insurance
Experience the best...

6
YEAR
WARRANTY
6 SAAL. AAPKA KHAYAL.

TATA
FleetMan
Fleet Telematics for higher productivity

TATA
Delight
Har Kadam Par Khusiyan

TATA
OK
TATA MOTORS Certified
PRE-OWNED COMMERCIAL VEHICLES

TATA
Genuine
Parts
Engineered to go the distance

TATA MOTORS
SURAKSHA
ANNUAL
MAINTENANCE
CONTRACT

TATA MOTORS
prolife
rebuilt to last

TATA
Kavach
QUICK ACCIDENT REPAIR

TATA
alert
Service-Anywhere, Anytime

Terms & Conditions apply

TATA MOTORS

For more information, please visit our website: www.tatatrucks.tatamotors.com
You can also contact our Sales Office: **Tata Motors Limited**, 4th Floor, Ahura Centre, 82, Mahakali Caves Road, MIDC, Andheri (East), Mumbai 400093 or call toll-free no. **18002097979**.

Terms & Conditions apply as per the policy of ITGI. Insurance available on light, intermediate & heavy commercial vehicles.
CAUTION: Accessories shown in the picture or elsewhere do not constitute standard fitment.
The specifications are merely indicative. Due to continuous product improvements, these specifications are liable to change without notice.

TATA MOTORS
Connecting Aspirations



DEPENDABILITY MEETS EFFICIENCY

LPT 2518

Now more Eco-friendly, Reliable and Fuel Efficient



Now available in Tilt Cabin version also

Now with Air Conditioning
or Truck Ventilation
System Options




Now with
Electronic Viscous Fan for
enhanced fuel economy



Images are representational

TATA 6-YEAR WARRANTY

Sampoorna khayal har kadam.



6 SAAL. AAPKA KHAYAL.

Terms & Conditions apply

Power of India's Most Reliable 3 Axle Rigid Truck


- Available in 3 deck lengths across 3 wheelbases:

4880/22.5ft | **Applications:** POL Tanker, Packed LPG, Parcel & Logistics
MLO, Construction Agg., Industrial Goods, Agri Produce
Edible Oil/Milk/Water Tanker, TMC, Drill Rig


5505/24.5ft | **Applications:** Packed LPG, Reefer, Poultry, Fishery

6750/32ft | **Applications:** White Goods, FMCG, E-commerce, Auto Logistics, Containerised Logistics, Reefer




- **Cummins ISBe 5.9 l engine** with Twin mode FE Switch, 2 stage fuel filtration, VAM, LBSC, GDP, E-Viscous Fan and Longer Oil drain intervals. Reduced maintenance cost with TMGO
 - **Trusted TATA G750 (FGR: 919)** and **Proven RA109RR (RAR: 5.57)** for superior torque at wheel and best-in-class fuel mileage under various road load conditions with enhanced driveability and low maintenance. Reduced maintenance cost with TMGO
 - **Cummins SCR after treatment system** - Clean, Safe, Robust & Reliable
 - Best in industry Durability, Reliability and Running Performance
 - PESO approval of 20KL for POL tanker on 2518 cowl and cab versions
- 

Comfortable seat and wide sleeper berth with



Easily navigable dashboard



Ergonomic instrument cluster



Comfortable seat and wide sleeper berth with foldable top berth



Easily navigable dashboard

Ergonomic
instrument cluster

TECHNICAL SPECIFICATIONS

LPT 2518

ENGINE	Engine Description	Cummins ISBe5.9 180 40 BS4 Common Rail	FRAME	Description	Ladder Type Heavy Duty Frame with Riveted/Bolted Cross Members
	Engine Capacity	5883 cm3		Dimensions	285 mm x 65 mm x 7 mm
CLUTCH	No. of Cylinders	6 Inline	BRAKES	Type	ABS
	Engine Output	132.5 kW @ 2500 r/min		Brake Drum Diameter	410 mm
GEARBOX	Torque	700 Nm at 1200-1600 r/min	STEERING	Front Brakes	Full Air S-cam with Automatic Adjuster
				Rear Brakes	Full Air S-cam with Automatic Adjuster
REAR AXLE	Clutch Details	Organic Standard & Cushioned Ceramic Optional	SUSPENSION	Service Brakes	Dual Circuit Full Air S-cam Brake
	Engine Clutch Type	Single Plate Dry Friction Type		Auxiliary Braking System	Engine Exhaust Brake
FRONT AXLE	Outside Diameter of Clutch Lining	380 mm	MAIN CHASSIS DIMENSIONS	Engine Exhaust Brake	Electro-Pneumatically Operated Coupled with Service Brake
	Type of Actuation	Push Type (Hydraulically actuated with Pneumatic Assistance)			
ELECTRICAL SPECIFICATION	Model	TATA G750 6-Speed	PERFORMANCE		
	First Gear Ratio	9.19			
WHEELS & TYRES	No. of Gears	6 (Forward) + 1 (Reverse)	WEIGHTS		
CLUTCH	Rear Axle Model	RA 109 RR	Overall Width	2440 mm	
	Rear Axle Description	Single speed, hypoid gear in pressed steel welded beam with differential carrier housing; Fully floating axle shafts			
GEARBOX	Rear Axle Ratio	5.57	Cowl	Cab	Cowl
	Rear Axle Type	RA 109 RR			
REAR AXLE	Front Axle Description	Extra Heavy Duty Forged I Beam, Reverse Elliot Type, ABS	Wheelbase	4880 mm	
	Front Axle Designed Capacity	6500 kg			
FRONT AXLE			Front Overhang	1260 mm	1515 mm
ELECTRICAL SPECIFICATION	Battery	12V x 2 = 24V x 100Ah	Overall Length	9010 mm	9264 mm
	Alternator Capacity	90A			
WHEELS & TYRES	Tyres	10 R 20 - 16PR	PERFORMANCE	Maximum Gradeability at Rated GVW 26%	
	Wheel Rims	Optional I: 7.50 x 20 Optional II: 7.50V x 20			
CLUTCH			WEIGHTS	Gross Vehicle Weight	25000 kg
				Maximum Permissible FAW	6000 kg
GEARBOX			Overall Width	Maximum Permissible RAW	19000 kg
REAR AXLE			Cowl	Cab	Cowl
FRONT AXLE			Wheelbase	4880 mm	
ELECTRICAL SPECIFICATION			Front Overhang	1260 mm	1515 mm
WHEELS & TYRES			Overall Length	9010 mm	9264 mm
CLUTCH			PERFORMANCE	Maximum Gradeability at Rated GVW 26%	
GEARBOX			WEIGHTS	Gross Vehicle Weight	25000 kg
				Maximum Permissible FAW	6000 kg
REAR AXLE			Overall Width	Maximum Permissible RAW	19000 kg
FRONT AXLE			Cowl	Cab	Cowl
ELECTRICAL SPECIFICATION			Wheelbase	4880 mm	
WHEELS & TYRES			Front Overhang	1260 mm	1515 mm
CLUTCH			Overall Length	9010 mm	9264 mm
GEARBOX			PERFORMANCE	Maximum Gradeability at Rated GVW 26%	
REAR AXLE			WEIGHTS	Gross Vehicle Weight	25000 kg
				Maximum Permissible FAW	6000 kg
FRONT AXLE			Overall Width	Maximum Permissible RAW	19000 kg
ELECTRICAL SPECIFICATION			Cowl	Cab	Cowl
WHEELS & TYRES			Wheelbase	4880 mm	
CLUTCH			Front Overhang	1260 mm	1515 mm
GEARBOX			Overall Length	9010 mm	9264 mm
REAR AXLE			PERFORMANCE	Maximum Gradeability at Rated GVW 26%	
FRONT AXLE			WEIGHTS	Gross Vehicle Weight	25000 kg
				Maximum Permissible FAW	6000 kg
ELECTRICAL SPECIFICATION			Overall Width	Maximum Permissible RAW	19000 kg
WHEELS & TYRES			Cowl	Cab	Cowl