

## TECHNICAL SPECIFICATIONS OF ULTRA 1014

MODEL	TATA ULTRA 1014
ENGINE MODEL	NG 3L BSIV
ENGINE TYPE	4 Cylinder In-line Water Cooled Direct, Injection Diesel Engine With Intercooler
FUEL INJECTION PUMP	Electronic Common Rail
POWER	103 kW (140 PS) @ 3000 rpm
TORQUE	360 Nm @ 1400 - 2000 rpm
CLUTCH TYPE & DIA	Single Plate Dry Friction Type (Booster-assisted) - 330 mm
GEARBOX	GB 550 (6F + 1R)
SUSPENSION	Front: Parabolic Leaf Springs, Rear: Semi-elliptical at Rear with Semi-elliptical Aux Springs
TYRES	235 / 75 R 17.5
STEERING TYPE	Hydraulic Power Assisted - Tilt and Telescopic
BRAKE TYPE	Dual Circuit Full Air S-Cam Brakes
GROUND CLEARANCE	189 mm
MAX SPEED	130 kmph (80 with speed limiter)
GRADEABILITY	28%
GVW	10400 kg
FAW	3400 kg
RAW	7000 kg
FRONT AXLE	10.4 T Front Axle "R" assy with Drum Air Brake
REAR AXLE	RA-1068, 34/7, W/S-Camm BRKS & non ABS
BATTERY	12V, 100 Ah
ALTERNATOR CAPACITY	90 Amps
FUEL TANK CAPACITY	160 l (45 WB)
EMISSION	BS IV

## DIMENSIONS

WHEEL BASE (in mm)	3310 mm			3920 mm			4530 mm		
STANDARD VARIANTS	CAB	CLB	HD	CAB	CLB	HD	CAB	CLB	HD
LENGTH (in mm)	4283	4283	4342	5197	8345	5062	6118	6118	6118
WIDTH (in mm)	2255	2255	2255	2255	2255	2255	2255	2255	2255
HEIGHT (in mm)	NA	919	2288	NA	835	2288	NA	837	2288
LOADING AREA	NA	9.04	9.82	NA	11.01	10.76	NA	12.98	12.69
TCD (m)	10800 mm			12900 mm			15200 mm		
DECK LENGTH	14 ft.			17 ft.			20 ft.		
WARRANTY	3 Years or 300000 km, Whichever is earlier*								

\*Conditions apply.



### Corporate Office:

Tata Motors Limited, 4th Floor, Ahura Centre, 82, Mahakali Caves Road, MIDC, Andheri (East), Mumbai 400093 | [www.tatamotors.com](http://www.tatamotors.com)  
Tel.: 022 62407101 / 022 62407109. Toll-free: 1800-209-7979 | Fax: 022 6240 7100

**TATA MOTORS**  
Connecting Aspirations



## ULTRA 1014 DIL SE QUICK

Turnaround time mein quick. Tarakki hogi quick.



DIL SE ULTRA

### MULTIPLE APPLICATIONS



LOGISTICS, GOODS  
& PARCELS



FRUITS & VEGETABLES



FISHERIES



AGRI PRODUCTS



MOULDED PLASTICS



FMCG